

2020 DEFENDER MAX X™ mr

HIGHLIGHTS

PLATFORM FEATURES

- 115.5-in. wheelbase
- 15-in. of ground clearance
- Dynamic Power Steering (DPS™)
- ECO™ / ECO Off / Work modes
- 2,500 lb towing capacity
- Multi-function cargo box with LinQ easy installation accessories
- Rear differential with Turf mode

SPECIFIC TO X mr PACKAGE

- 64-in. wide with Arched A-arm
- Smart-Lok™** front differential
- Strategically positioned engine air intake and CVT inlet / outlet
- 14-in. cast-aluminum wheels
- VERSA-PRO bench seat with bolster seats, reinforced seat skin featuring X package trims and adjustable driver seat
- HMWPE full skid plate
- 4,500-lb (2,014 kg) winch with synthetic rope
- Heavy-duty front steel bumper
- Full hard roof
- Aluminum rock slider
- 7.6 in. digital display with keypad
- Brake holding mechanism

TOUGH

- Heavy-duty Rotax® engine
- Smooth, durable and responsive transmission
- True Can-Am DNA with a strong identity

CAPABLE

- Work or ride with confidence
- Meaningful and versatile functionality
- Easy handling and capabilities

CLEVER

- Advanced comfort and intuitive cockpit with optimized visibility
- Multifunction cargo box with sturdy tailgate and smart storage
- 1-year maintenance free and easy access to key maintenance components



Mossy Oak† Break-Up Country Camo† / HD10



ENGINES

HD10

Type	82 hp / 69 lb-ft, Rotax® 976 cc, V-twin, liquid cooled with strategically positioned engine air intake
Fuel Delivery System	Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)
Transmission	PRO-TORQ transmission with Quick Response System (QRS), high airflow ventilation and Electronic Drive Belt Protection Extra-L / H / N / R / P
Drive Train	Selectable Turf Mode / 2WD / 4WD TRAIL / 4WD MUD with exclusive Smart-Lok** technology. <small>**Smart-Lok was developed in conjunction with TEAM Industries, a market leader in the drive train industry</small>
Driving Assistance	Electronic Hill Descent Control ECO / ECO Off / Work modes
Power Steering	Dynamic Power Steering (DPS)

SUSPENSIONS

Front Suspension	Arched double A-arm with sway bar / 10 in. (25.4 cm) travel
Front Shocks	Twin tube gas charged shocks
Rear Suspension	Arched TTA with external sway bar / 10 in. (25.4 cm) travel
Rear Shocks	Twin tube gas charged shocks

BRAKES

Front	Dual 220 mm ventilated disc brakes with hydraulic twin-piston calipers
Rear	Dual 220 mm ventilated disc brakes with hydraulic twin-piston calipers Brake holding mechanism

TIRES / WHEELS

Front Tires	ITP†* Cryptid† 30 x 9 x 14 in. (76.2 x 22.9 x 35.6 cm)
Rear Tires	ITP* Cryptid 30 x 11 x 14 in. (76.2 x 27.9 x 35.6 cm)
Wheels	14-in. (35.6 cm) cast-aluminum

FEATURES

Gauge	7.6 in. (19.3 cm) wide digital display with keypad: Speedometer, tachometer, odometer, trip and hour meters, fuel, gear position, ECO / ECO Off / Work modes, seat belt, diagnostics, clock, battery voltage, engine temperature	Seat	Dual VERSA-PRO bench seats with bolster seats for additional lateral support, passenger seats flipping up, adjustable driver seat, underside hooks, reinforced seat skin featuring X package trims and contoured bench to improve entrance/exit of the cab
Instrumentation	Lighter type DC outlets in the console (20-A) and two USB port in the dash storage	Lighting	140 W lighting output from four 35-W reflectors ensuring a wide visibility and LED tail lights
Winch	4,500-lb (2,041 kg) winch with synthetic rope and roller fairlead	Protection	Heavy-duty front steel bumper, HMWPE full skid plate, aluminum rock sliders, mudguards
Battery	12 V (30 amp/h)	Hitch Type	2-in. hitch receiver
Magneto	650 W	Steering Wheel	Adjustable tilt steering

WARRANTY

Factory	1-year limited warranty
Extended	Up to 30 months B.E.S.T. coverage

DIMENSIONS / CAPACITIES

L x W x H	161.9 x 64 x 82 in. (411.2 x 162.5 x 208.3 cm)
Wheelbase	115.5 in. (294 cm)
Ground Clearance	15 in. (38.1 cm)
Estimated Dry Weight	1 999 lb (906.7 kg)
Cage	Profiled cage ROPS approved
Cargo Box Dimensions	38 x 54.5 x 12 in. (96.5 x 138.4 x 30.5 cm)
Cargo Box Capacity	1,000 lb (454 kg) / California only: 600 lb (272.2 kg)
Tailgate Load Capacity	250 lb (113.4 kg)
Storage Capacity	Total: 16.9 gal (63.9 L) Under dash: 6 gal (22.8 L) Waterproof and removable box under passenger seat: 5.6 gal (21 L) Dash: 2 gal (7.7 L) Water-resistant and removable toolbox: 1.7 gal (6.3 L) Armrests and cup holders: 1.6 gal (6.1 L)
Towing Capacity	2,500 lb (1134 kg)
Payload Capacity	1,650 lb (750 kg)
Fuel Capacity	10.6 gal (40 L)
Person Capacity	6

BEST PROTECTION ©2019 Bombardier Recreational Products Inc (BRP). All rights reserved. TM, ® and the BRP logo are trademarks of Bombardier Recreational Products Inc. or its affiliates. In the U.S.A., the products are distributed by BRP US Inc. †Visco-Lok is a trademark of GKN Viscodrive GmbH. †All other trademarks are the property of their respective owners. BRP reserves the right, at any time, to discontinue or change specifications, prices, designs, features, models or equipment without incurring obligation. Some models depicted may include optional equipment. Read the side-by-side vehicle (SSV) Operator's Guide and watch the Safety DVD before driving. For your safety: wear a helmet, eye protection and other protective gear. Fasten lateral net and seat belt at all times. Always remember that riding and alcohol/drugs don't mix. SSV is for off-road use only. Never ride on paved surfaces or public roads. Operator must be at least 16 years old. Passenger must be at least 12 years old and able to hold handgrips and plant feet while seated against the backrest. Never engage in stunt driving and avoid excessive speed.

can-am.



Can-AmOffroad.com